

# Brass Service Valve

Durable brass service valve allows isolation of a fixture or appliance for emergency or maintenance work

## Overview

Speedfit brass push-fit inline service valve for connecting plastic or copper pipe. Using a tamperproof 1/4 turn screwdriver slot, the valve enables the flow of water to a fixture to be isolated in the event of an emergency or for maintenance work. Simply push the valve fully onto the pipe. To demount the connection, push the collet towards the body of the fitting and pull the pipe release.

The fitting is up to 40% faster to install than traditional methods and is easier to use in confined spaces by removing the need for hot works and tools.

Designed, manufactured and assembled in the UK.

## Features & Benefits

- Durable DZR brass body is ideal for surface mounted pipework
- 1/4 turn isolation screwdriver slot
- Safe flame-free installation, with no hot works, glue or flux
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot and cold water and central heating systems



Product code	Description	Size	Bag QTY
15HSV-BRASS	Brass Service Valve	15mm	1

## Working parameters & specifications

Application	Usual working temperature °C	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	20	12
Hot Water (including unvented cylinders)	65	95	6

## Materials

Body	Brass CW614N
O-Ring & Seals	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Acetal Copolymer (Unfilled), Dark Grey
Collet Teeth	Stainless Steel 301
Support Washer	Acetal Copolymer (Unfilled), Natural
Actuating Ball	Chrome Plated Brass CW614N

## Dimensions – All measurements in mm unless otherwise stated

