

Stem Elbow

Easily connects two MDPE fittings of unequal size to create a swivel type 90° connection

Overview

Speedfit push-fit fitting to connect MDPE pipe. The uniquely designed fitting incorporates a stem end for connecting two Speedfit fittings and stainless teeth to provide a tight and secure grip on the pipe. Simply push the fitting fully onto the pipe. The connection is demountable, making it easy to work with in the ground when maintaining or altering an existing set-up.

The fitting is up to 40% faster to install than traditional methods and is easier to use in confined spaces by removing the need for hot works and tools.

Designed, manufactured and assembled in the UK.



Features & Benefits

- Instant push-fit connection
- Install and demount in seconds without tools
- Stainless steel teeth grab ring provides extra grip on the pipe
- Durable material with high impact resistance
- Non-toxic and no scale build-up
- Resists corrosion and biological growth
- Compatible with MDPE pipes only (inserts required)
- Suitable for cold water use only

Product code	Description	Pipe	Stem	Bag QTY
UG222025B	Cold Water Service Stem Elbow	20mm	25mm	1
UG222525B	Cold Water Service Stem Elbow	25mm	25mm	1
UG223232B	Cold Water Service Stem Elbow	32mm	32mm	1



JG Speedfit Stem Elbow

Working parameters & specifications

Application	Usual working temperature °C	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	20	16

Materials	
Body	Polypropylene (Glass Filled), Black
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Acetal Copolymer (Unfilled) Blue
Collet Teeth	Stainless Steel
Collet Cover	Acetal Copolymer (Unfilled) Blue
Support Washer	Acetal Copolymer (Unfilled) Blue

Dimensions – All measurements in mm unless otherwise stated

