

# Slip Tee Connector

Adjustable ended slip type pipe coupler for the connection of two equally sized pipes

## Overview

Speedfit plastic push-fit fitting that allows pipe runs to be branched off an existing pipe run without impacting the existing set up. The slip tee connector is an ideal tool should radiators or other applications need to be added during a refurbishment project. Simply push the fitting fully onto the pipe and twist the plastic nut clockwise to lock in place.

To demount the connection, unlock the nut by hand and push the collet towards the body of the fitting and pull the pipe to release. The fitting is up to 40% faster to install than traditional methods and is easier to use in confined spaces by removing the need for hot works and tools.

Designed, manufactured and assembled in the UK.

## Features & Benefits

- Instant push-fit connection
- Install and demount in seconds without tools
- Safe flame-free installation, with no hot works, glue or flux
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Non-toxic, resists corrosion and no scale build-up
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot, cold and central heating applications



Product code	Description	Size	Bag QTY
15TKP	Slip Tee Connector	15mm	1
22TKP	Slip Tee Connector	22mm	1



50 year guarantee when used with JG Speedfit Layflat PB and PEX Barrier Pipes

# Slip Tee Connector

Application	Usual working temperature °C	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	20	12
Central Heating	82	105, short term malfunction at 114	3
Hot Water (including unvented cylinders)	65	95	6

Materials	
Body	X-Linked Polyethylene, White
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Nylon
Collet Teeth	Stainless Steel 301
Caps	Nylon (40% Mineral Filled), White
Compression Ring	Acetal Copolymer, White

**Dimensions** – All measurements in mm unless stated

