

Speedfit x Plain Stem Flexi Hose

Connects a supply to a tap or other fixture or appliance

Overview

Speedfit push-fit flexi hose with a stem for the connection of plastic and copper pipe. Simply push the fitting fully onto the pipe and screw the nut onto the thread of the appliance. To demount the push-fit end, push the collet towards the body of the fitting and pull the pipe release.

The fitting is quicker and easier to install in confined spaces than traditional methods as it eliminates the need for hot works or tools.

Designed, manufactured and assembled in the UK.

Features & Benefits

- An alternative to hard piping to a tap or fixture
- Flexible design makes installation hassle free
- Safe flame-free installation, with no hot works, glue or flux
- Braided stainless steel outer layer protects the internal feed from damage
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot and cold water only (6 Bar @ 65 °C)

Part Code	Description	Size	Bag QTY
FLX53	Speedfit x Plain Stem	15 x 15mm	2

Working parameters & specifications

Application	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	10
Hot Water (including unvented cylinders)	65	6

Materials

Tube x Hose Stem	Nickel Plated Brass
Ferule ID	Stainless Steel
Braided Hose	Ethylene Polypropylene (EPDM) & Stainless Steel
Ferule	Stainless Steel
Connector Body	Acetal Copolymer (Unfilled), Light Grey
Collet	Acetal Copolymer (Unfilled), Grey & Stainless Steel
Support Washer	Acetal Copolymer (Unfilled), Natural
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)



Dimensions – All measurements in mm unless otherwise stated



50 year guarantee when used with JG Speedfit Layflat PB and PEX Barrier Pipes