

Speedfit x Speedfit Flexi Hose

Connects a supply to a tap or other fixture or appliance

Overview

Speedfit push-fit flexi hose for the connection of plastic or copper pipe. The white PVC hose material significantly reduces the hose 'kinking' and makes the product easier to clean. Simply push the fitting fully onto the pipe. To demount the connection, push the collet towards the body of the fitting and pull the pipe release.

The fitting is quicker and easier to install in confined spaces than traditional methods as it eliminates the need for hot works or tools.

Designed, manufactured and assembled in the UK.

Features & Benefits

- An alternative to hard piping to a tap or fixture
- Flexible design makes installation hassle free
- Safe flame-free installation, with no hot works, glue or flux
- White PVC design stops the pipe kinking and makes cleaning easier
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot and cold water only (6 Bar @ 65 °C)



Product code	Description	Size	Bag QTY
300mm			
WFLX33	Speedfit x Speedfit	15 x 10mm	2
WFLX17	Speedfit x Speedfit	15 x 15mm	2
500mm			
WFLX21	Speedfit x Speedfit	15 x 15mm	2



50 year guarantee when used with JG Speedfit Layflat PB and PEX Barrier Pipes

JG Speedfit x Speedfit

Working parameters & specifications

Application	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	12
Hot Water (including unvented cylinders)	65	6

Materials

Body	Acetal Copolymer (Unfilled) White
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Acetal Copolymer (Unfilled) White
Collet Teeth	Stainless Steel
Ferule	Stainless Steel
Flexible Hose	Multi-Layered PVC, Polyester Fibre Reinforced & Hytel

Dimensions – All measurements in mm unless otherwise stated

