

Black Bodied Single O-Ring Seal Unequal Connector

Safely and securely connects un-equally sized microduct pipe

Overview

The JG Blown Fibre Black Bodied Single O-Ring Seal Unequal Connector is designed for simple installation and seamless performance under the toughest of conditions. It's black colour gives added UV protection for the microduct pipe. Featuring a collet with stainless steel teeth, the fitting is designed to provide a secure connection with a simple push-fit action.

This technology eliminates the need for any tools, making the installation process efficiently straightforward. In the event of repair or network expansion works, the JG Blown Fibre Black Bodied Single O-Ring Seal Unequal Connector provides superior installation flexibility, as the demountable feature of the solution allows for the system to be reconfigured at any given time without damage to the microduct or fitting.



Features and benefits

- Black surface gives extra UV protection
- Hard wearing construction for installation into the toughest of conditions
- Push-fit technology ensures swift tool-free installation
- Collet with stainless steel teeth securely locks microduct in place
- O-Ring Seals enhance connection integrity

Product code	Description	Size
NC2558	Black bodied Single O-Ring Seal Unequal Connector	6 x 3mm



Blown fibre fittings

Black Bodied Single O-Ring Seal Unequal Connector

Working pressures & temperatures

Blowing pressure (max)	16 bar
Temperature range	-25°C to 60 °C

Applications

Direct buried fibre optic microducts	✓
--------------------------------------	---

Materials

Body	Acetal Copolymer (Unfilled)
Collets & Cartridges	Polypropylene (Unfilled), Black & Stainless Steel
O-Ring	Nitrile, Black

Dimensions


Dimensions in mm