Underfloor Heating



JG Underfloor 240v Wired RF Programmable Thermostat

RF Wireless controlled programmable room thermostat for underfloor heating

Overview

JG Underfloor Controls 240v wired and RF programmable thermostat is a stylish and simple way to control wet underfloor heating systems.

The thermostat is mains-powered but communicates with the JG Underfloor Controls RF wiring centre via a radio signal to provide heat to an individual room and to remove the need for further wiring. Its user-friendly interface makes adjusting and programming temperatures fast and simple.


Ideal for new builds and renovations, the back plate is fitted before decorating begins and the front plate is installed once work is completed to avoid any damage. Designed to suit a standard pattress box, the thermostat is also ideal when replacing an existing thermostat.

When used with the JG Underfloor Controls gateway and app, underfloor heating can be remotely controlled on the go.

Features & benefits

 Mains-powered RF programmable thermostat that is easy to install and set up

| Product code | Description Page | ck QTY |
|------------------------------|--|--------|
| JGSTAT RF4 W | JG Underfloor 240v RF Thermostat (White) | 1 |
| JGSTAT RF4 B L | JG Underfloor 240v RF Thermostat (Black) | 1 |



| 200 |
|-----|
| |
| |








JG Underfloor Controls 240v Wired RF Programmable Thermostat

| Working pressures & tempera | tures | |
|-----------------------------|---|--|
| Туре | Programmable Room Thermostat | |
| Power Supply | 240v AC50/60 Hz | |
| Programming Modes | 7 day | |
| Program Number | Up to 6 events | |
| Accuracy | +/- 0.5°C | |
| Frost Protection | Adjustable from 5-17°C (Factory Setting 10°C) | |
| Open Window Function | Selectable option | |
| Temperature Scale | 5-35°C | |
| System Optimization | Selectable option | |
| External Sensor | NTC10K | |
| Boost Override | 1-9 hour boost function | |
| Screen Lock | Selectable option | |
| Holiday Mode | In app selectable option | |
| Relay Contactor | 250V 3A | |
| RF Wireless Signal | 868 Mhz Lora system | |
| WI-FI | 2.4 Ghz | |
| App Download Source | IOS & Android | |

| Applications | | |
|--------------------|---|--|
| Underfloor heating | √ | |

Approvals





| Product code | Α | В | С |
|--------------|----|----|----|
| JGSTATRF4W | 35 | 86 | 86 |
| JGSTATRF4BL | 35 | 86 | 86 |