

Transparent Body Gas Block Connector

**Connects blown fibre/minicable
micro ducting**

Overview

The John Guest Blown Fibre Superseal Connector provides a simple and effective gas seal between the pipe and the fibre bundle or mini cable, eliminating the need for sealing resin. The connector through bore an uninterrupted passage for the blown fibre/mini cable.

Colours available - Suffix indicates colours GB=Green, BB = Blue, RB = Red

Features and benefits

- Transparent centre core for easy inspection
- Hard wearing construction for installation into the toughest of conditions
- Push-fit technology ensures swift tool-free installation
- Eliminates the need for sealing resin
- Collet with stainless steel teeth securely locks microduct in place
- O-Ring Seals enhance connection integrity



Product code	Description	Size
NC2657GB	Clear Body Connector	7mm
NC2657RB	Clear Body Connector	7mm
NC2657BB	Clear Body Connector	7mm



Transparent Body Gas Block Connector

Working pressures & temperatures

Blowing pressure (max)	16 bar
Temperature range	-25°C to 60 °C

Applications

Direct buried fibre optic microducts	✓
--------------------------------------	---

Materials

Body	Acetal Copolymer (Unfilled),
Collets & Cartridges	Acetal Copolymer(Unfilled), Stainless Steel
O-Ring	Nitrile, Black
Caps	Acetal Copoloymer (Unfilled), Yellow

Dimensions

