

Ring Type - Squeeze to Ring Release

**Connects blown fibre/minicable
micro ducting**

Overview

The John Guest Blown Fibre Ring Type Squeeze to Release Connector provides a simple and effective gas seal between the pipe and the fibre bundle or mini cable, eliminating the need for sealing resin. The connector through bore an uninterrupted passage for the blown fibre/mini cable.

Suffix indicates colours available - GB=Green, BB = Blue, RB = Red

Features and benefits

- Coloured surface gives extra UV protection
- Hard wearing construction for installation into the toughest of conditions
- Push-fit technology ensures swift tool-free installation
- Eliminates the need for sealing resin
- Collet with stainless steel teeth securely locks microduct in place
- O-Ring seals enhance connection integrity

Product code	Description	Size
NC2525	Ring Type - Squeeze to Release	4mm x 4mm
NC2559	Ring Type - Squeeze to Release	6mm x 3mm
NC2526	Ring Type - Squeeze to Release	6mm x 4mm
NC2676	Ring Type - Squeeze to Release	6mm x 6mm



International patents applied for

UK patents pending: 1909903.5/1909909.2/1909906.8
Worldwide design registrations pending



Ring Type - Squeeze to Release

Working pressures & temperatures

Blowing pressure (max)	16 bar
Temperature range	-25°C to 60 °C

Applications

Direct buried fibre optic microducts	✓
--------------------------------------	---

Materials

Body	Acetal Copolymer (Unfilled)
Collets & Cartridges	Acetal Copolymer (Unfilled), Stainless Steel
O-Ring	Nitrile, Black
Caps	Acetal Copolymer (Unfilled), Yellow

Dimensions

