

JG LowFit™ Fibre Mesh Panel 16mm (for 12mm Pipe)

A low-profile mesh covered panel that provides a high output with direct application of ceramic or stone floor coverings using 12mm JG Layflat Polybutylene Pipe.

Overview

JG LowFit™ Mesh Panels are designed to be installed over existing timber or concrete floors, while maintaining a low overall floor height.

The 16mm panel is lightweight with high compressive strength. The mesh layer allows for tiling directly to the panel* and is pre-grooved to include return bends that eliminate the need for additional panel variations.

Features & benefits

- Ideal solution for laying over existing timber or concrete floors
- Suitable for single or multi-rooms
- Easy to install low profile 16mm panel for 12mm pipe
- Lightweight panel with high compressive strength
- High heat output from a low-level floor build
- Return bends are indented into the panel for easy installation
- Mesh layer allows for tiling directly to the panel ensuring a low overall floor height*
- Made from 100% recyclable material

* In some cases, a decoupling layer may be required, always consult the flooring supplier for advice.



Product Code	Pack Quantity	Description	Pipe Compatibility
JGLOWFIT16M	10	JG LowFit™ Mesh Panel 16mm	12mm



JG LowFit™ Fibre Mesh Panel 16mm (for 12mm Pipe)

Working parameters & specifications

Compressive strength	400kPa at 10% compression
Conductivity	0.035W/mk
Maximum circuit length	80m
Effective coverage	0.75m ²
Pipe spacing	150mm
Pipe size	12mm

Applications

Underfloor Heating

Materials

Panels Mesh covered extruded polystyrene-XPS2

Floor coverings

Tiles, slate or ceramic, etc. Direct application using suitable adhesive and decoupling membrane if required

Dimensions – All measurements in mm unless otherwise stated

